



LØFTETABELL FOR HAMAS FIBERSTROPPER

RUNDSLING OG BÅNDSTROPPER

Wenaas
avd. **LOCHNER**
Tlf. 38 14 88 00 Box 1574 4688 KR.SAND

Sikkerhetsfaktor 7:1 Safety factor 7:1	Rett strekk Straight lift	Snaret Choked lift	U - løft Basket hitch			2-parter 2-leg sling		3 og 4 parter 3 and 4-leg sling	
			Parallell	$\beta = 0 - 45^\circ$	$\beta = 46 - 60^\circ$	$\beta = 0 - 45^\circ$	$\beta = 46 - 60^\circ$	$\beta = 0 - 45^\circ$	$\beta = 46 - 60^\circ$
WLL in tonn / ton	t	t	t	t	t	t	t	t	t
Fiolett / Violet	1,0	0,8	2,0	1,4	1,0	1,4	1,0	2,1	1,5
Grønn / Green	2,0	1,6	4,0	2,8	2,0	2,8	2,0	4,2	3,0
Gul / Yellow	3,0	2,4	6,0	4,2	3,0	4,2	3,0	6,3	4,5
Grå / Grey	4,0	3,2	8,0	5,6	4,0	5,6	4,0	8,4	6,0
Rød / Red	5,0	4,0	10,0	7,0	5,0	7,0	5,0	10,5	7,5
Brun / Brown	6,0	4,8	12,0	8,4	6,0	8,4	6,0	12,6	9,0
Blå / Blue	8,0	6,4	16,0	11,2	8,0	11,2	8,0	16,8	12,0
Orange / Orange	10,0	8,0	20,0	14,0	10,0	14,0	10,0	21,0	15,0
Faktor symmetrisk Factor symmetrical	1,0	0,8	2,0	1,4	1,0	1,4	1,0	2,1	1,5

For opplysninger om anbefalt ANLEGGSDIAMETER, se egen info. om HAMAS løftestropper