


6x36+FC

Galvanisert / Galvanized



| NOM ROPE DIA. (mm) | Weight per KG | mtr | EN 12385 MBL in kN 1770 N/mm ² | EN 12385 MBL in kN 1960 N/mm ² |
|--------------------------|------------------|-----|---|---|
| 6 | 0,132 | | 21,0 | 23,3 |
| 7 | 0,180 | | 28,6 | 31,7 |
| 8 | 0,235 | | 37,4 | 41,4 |
| 9 | 0,297 | | 47,3 | 52,4 |
| 10 | 0,367 | | 58,4 | 64,7 |
| 11 | 0,444 | | 70,7 | 78,3 |
| 12 | 0,528 | | 84,1 | 93,1 |
| 13 | 0,620 | | 98,7 | 109,3 |
| 14 | 0,719 | | 114,5 | 126,8 |
| 15 | 0,826 | | 131,4 | 145,5 |
| 16 | 0,940 | | 149,5 | 165,6 |
| 18 | 1,189 | | 189,2 | 209,6 |
| 19 | 1,325 | | 210,9 | 233,5 |
| 20 | 1,468 | | 233,6 | 258,7 |
| 22 | 1,776 | | 282,7 | 313,1 |
| 24 | 2,114 | | 336,4 | 372,6 |
| 26 | 2,481 | | 394,9 | 437,2 |
| 28 | 2,877 | | 457,9 | 507,1 |
| 30 | 3,303 | | 525,7 | 582,1 |
| 32 | 3,758 | | 598,1 | 662,3 |
| 34 | 4,243 | | 675,2 | 747,7 |
| 36 | 4,756 | | 757,0 | 838,3 |
| 38 | 5,299 | | 843,4 | 934,0 |
| 40 | 5,872 | | 934,6 | 1034,9 |




6x36+IWRC

Galvanisert / Galvanized



| NOM ROPE DIA. (mm) | Weight per KG | mtr | EN 12385 MBL in kN 1960 N/mm ² |
|--------------------------|------------------|-----|---|
| 6 | 0,147 | | 25,1 |
| 7 | 0,200 | | 34,2 |
| 8 | 0,261 | | 44,7 |
| 9 | 0,332 | | 56,5 |
| 10 | 0,408 | | 69,8 |
| 11 | 0,494 | | 84,4 |
| 12 | 0,588 | | 100,5 |
| 13 | 0,692 | | 117,9 |
| 14 | 0,802 | | 136,8 |
| 15 | 0,921 | | 157,0 |
| 16 | 1,040 | | 178,6 |
| 18 | 1,320 | | 226,1 |
| 19 | 1,470 | | 251,9 |
| 20 | 1,630 | | 279,1 |
| 21,7 | 1,917 | | 328,6 |
| 22 | 1,970 | | 337,7 |
| 24 | 2,350 | | 401,9 |
| 26 | 2,760 | | 471,7 |
| 28 | 3,200 | | 547,0 |
| 30 | 3,670 | | 628,0 |
| 32 | 4,180 | | 714,5 |
| 34 | 4,720 | | 806,6 |
| 36 | 5,310 | | 904,3 |
| 38 | 5,890 | | 1007,6 |
| 40 | 6,550 | | 1116,4 |
| 42 | 7,230 | | 1230,8 |
| 44 | 7,930 | | 1350,9 |
| 48 | 9,430 | | 1607,6 |
| 52 | 11,11 | | 1886,7 |
| 56 | 12,81 | | 2188,2 |
| 64 | 16,73 | | 2858,0 |
| 77 | 24,21 | | 4137,0 |




HYFLEX 35x7

Galvanisert / Galvanized



| NOM ROPE DIA. (mm) | Weight per mtr KG | FACTORY STANDARD MBL in kN 1960 N/mm2 | FACTORY STANDARD MBL in kN 2160 N/mm2 |
|--------------------|-------------------|--|--|
| 10 | 0,448 | 76,0 | 86,5 |
| 11 | 0,542 | 91,0 | 104,0 |
| 12 | 0,645 | 107,0 | 125,0 |
| 13 | 0,760 | 128,0 | 146,0 |
| 14 | 0,880 | 148,0 | 168,0 |
| 15 | 1,01 | 169,9 | 192,9 |
| 16 | 1,15 | 194,0 | 221,0 |
| 18 | 1,45 | 242,0 | 277,0 |
| 19 | 1,62 | 277,0 | 312,0 |
| 20 | 1,79 | 301,0 | 337,0 |
| 21 | 1,98 | 335,0 | 370,0 |
| 22 | 2,17 | 370,0 | 412,0 |
| 24 | 2,58 | 441,0 | 498,0 |
| 26 | 3,03 | 517,0 | 581,0 |
| 28 | 3,51 | 599,0 | 681,0 |
| 30 | 4,03 | 679,0 | 775,0 |
| 32 | 4,59 | 769,0 | 865,0 |
| 34 | 5,18 | 868,0 | 976,0 |
| 36 | 5,81 | 983,0 | 1085,0 |




6x12+7FC

Galvanisert / Galvanized



| NOM ROPE DIA. (mm) | Weight per KG | mtr | BS 302 MBL in kN 1770 N/mm ² |
|--------------------------|------------------|-----|---|
| 3 | 0,026 | | 3,33 |
| 4 | 0,037 | | 5,88 |
| 5 | 0,058 | | 9,22 |
| 6 | 0,090 | | 13,34 |
| 8 | 0,148 | | 23,63 |



6x19+FC

Galvanisert / Galvanized




| NOM ROPE DIA. (mm) | Weight per KG | mtr | EN 12385 MBL in kN 1770 N/mm ² |
|--------------------------|------------------|-----|---|
| 3 | 0,031 | | 4,89 |
| 4 | 0,055 | | 8,70 |
| 5 | 0,087 | | 13,6 |
| 6 | 0,125 | | 19,6 |
| 7 | 0,170 | | 26,6 |
| 8 | 0,221 | | 34,8 |
| 9 | 0,280 | | 44,0 |
| 10 | 0,346 | | 54,3 |
| 11 | 0,419 | | 65,8 |
| 12 | 0,498 | | 78,2 |
| 13 | 0,585 | | 91,8 |
| 14 | 0,678 | | 106,5 |
| 16 | 0,886 | | 139,1 |
| 18 | 1,121 | | 176,1 |
| 20 | 1,384 | | 217,4 |
| 22 | 1,675 | | 263,0 |



Stainless 7x19 (AISI 316)


| NOM ROPE DIA. (mm) | Weight per KG mtr | EN 12385 MBL in kN 1570 N/mm2 |
|--------------------------|-------------------------|-------------------------------------|
| 2 | 0,015 | 2,27 |
| 3 | 0,034 | 5,12 |
| 4 | 0,061 | 9,09 |
| 5 | 0,095 | 14,21 |
| 6 | 0,137 | 20,46 |
| 7 | 0,187 | 27,85 |
| 8 | 0,244 | 33,36 |
| 10 | 0,381 | 52,12 |



Stainless 6x36+IWRC (AISI 316)



| NOM ROPE DIA. (mm) | Weight per KG mtr | EN 12385 MBL in kN 1570 N/mm2 |
|--------------------------|-------------------------|-------------------------------------|
| 10 | 0,409 | 55,9 |
| 12 | 0,589 | 80,5 |
| 13 | 0,691 | 94,5 |
| 14 | 0,802 | 109,5 |
| 16 | 1,047 | 143,1 |
| 18 | 1,325 | 181,1 |
| 20 | 1,636 | 223,6 |
| 22 | 1,980 | 270,5 |
| 24 | 2,356 | 321,9 |
| 26 | 2,765 | 377,8 |



Stainless 7x7 (COATED)



| NOM ROPE DIA. (mm) | Weight KG per mtr | EN 12385 MBL in kN 1570 N/mm2 |
|--------------------------|----------------------------|-------------------------------------|
| 4,0/6,0 | 0,061 | 9,02 |